



The Tower water filtration unit is delivered to you fully assembled, washed and ready to use. Just quickly rinse all the parts to remove potential packaging dusts and you can start using your Tower.



The aquacristal filter cartridge must be rinsed with clean fresh water prior to first use. Place the assembled top tank(b) and cartridge(c) over the bottom tank(a) and run a full top tank (4L) through the cartridge. Then empty and rinse the bottom tank. Fill the top tank and start using.

MAINTENANCE INSTRUCTIONS

1. Wash all parts (except the filter cartridge) in soapy water. Rinse. Dry.



2. Insert the thicker lip of the silicone joint(d) through the bottom opening of the top tank(b). Then wet and slide the cartridge(c) into the silicone joint(d) and push down until the glass lip touches the silicone.


3. Insert one stainless steel washer and one silicone washer onto the tap(e). Then insert the tap into the bottom tank and thread the other silicone washer and stainless steel washer onto the tap.



4. Secure by screwing the stainless steel ring in place. Hold the ring in place while using the tap to tightly screw everything together.



6. Fill the top tank with water and let it filter through the filter cartridge. Then fill the top tank a second time. Please make sure to not overflow your unit or it will overflow. Always make sure there is enough empty space in the bottom tank before adding more water to the top tank.



5. Place the bottom tank(a) onto its stand. Now place the top tank(b) onto the bottom tank(a).

